

Countertop Fryer W.FRSxx / W.FRTxx

Product Information:

- Mechanical thermostat temperature control
- Designed for 180°C frying
- Suitable for use with liquid oil only
- Over temperature safety cut-out as standard
- Stainless steel element covers
- Basket holder at rear for draining
- Removable splash guard
- Removable tilting element assembly
- Easily removable oil tank
- Snug fitting stainless steel tank cover
- Drip tray supplied complete with basket(s)
- Power on and indicator light



Specifications:

Model	W.FRS50	W.FF
Height	355mm	384m
Width	285mm	285m
Depth	483mm (619mm with basket)	483m
Power	2.2kW	3.2kV
	10A plug & lead fitted	15A p
Capacity	5 Litre	8 Litr
	8.5kg/hr (frozen 10mm chips)	11.5k


Model W.FRT50 Height 355mm Width 550mm Depth 483mm (619mm with basket) Power 2 x 2.2kW 2 x 10A plug & lead fitted *2 separate 10A circuits Capacity 2 x 5 Litre 2 x 8.5kg/hr (frozen 10mm chips)


W.FRS80


384mm 285mm 483mm (619mm with basket) 3.2kW 15A plug & lead fitted 8 Litre 11.5kg/hr (frozen 10mm chips)

W.FRT80

384mm 550mm 483mm (619mm with basket) 2 x 3.2kW 2 x 15A plug & lead fitted *2 separate 15A circuits 2 x 8 Litre 2 x 11.5kg/hr (frozen 10mm chips)











Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: C - 25/05/2022 - 01

www.stoddart.com.au www.stoddart.co.nz