airex∋

AXR.UCGN.2G

Refrigerated Undercounter 2 Glass Doors - 1/1GN

Product Information:

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C 6°C)
- Fan forced ducted cooling for uniformed performance throughout
 the entire refrigerator
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard
- 1/1GN shelf configuration with adjustable runners
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Double glazed heated glass door for exceptional display and minimal condensation
- Self-closing doors with lock fitted as standard
- Supplied on standard and lockable castors for a 840mm finish height. Optional spacer to increase to 900mm working height
- 3 and 4 door models also available, with glass or solid doors

Designed and Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty


Optional Accessories:

- Height increase channel spacer pair (AXR.UCGN.CH) (2 required)
- 1/1GN shelf with runners (AXR.UCGN.SHELFKIT)

Specifications

AXR.UCGN.2G
1360 x 700 x 840
107kg
1390 x 730 x 880
126kg
184 Litres
0°C - 6°C
R290
4
38°C
230VAC / 50Hz / 0.33kW 10A plug & lead

1360





Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: A - 19/09/2022 - 03 WWW.stoddart.com.au WWW.stoddart.co.nz

