# oirex<del>=</del>

## AXR.UCGN.3G

**Refrigerated Undercounter** 3 Glass Doors - 1/1GN

### **Product Information:**

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C 6°C) •
- Fan forced ducted cooling for uniformed performance throughout the entire refrigerator
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility .
- Stainless Steel worktop as standard
- 1/1GN shelf configuration with adjustable runners .
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative • internal design
- High quality components including highly efficient compressors • and EC fans
- Double glazed heated glass door for exceptional display and minimal condensation
- Self-closing doors with lock fitted as standard
- Supplied on standard and lockable castors for a 840mm finish height. Optional spacer to increase to 900mm working height
- 2 and 4 door models also available, with glass or solid doors

#### Designed and Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty


#### **Optional Accessories:**


- Height increase channel spacer pair (AXR.UCGN.CH) (2 required) •
- 1/1GN shelf with runners (AXR.UCGN.SHELFKIT) •

#### **Specifications**

| Model                  | AXR.UCGN.3G                      |
|------------------------|----------------------------------|
| W x D x H (mm)         | 1795 x 700 x 84                  |
| Weight                 | 133kg                            |
| Packed Dimensions (mm) | 1825 x 730 x 88                  |
| Packed Weight          | 157kg                            |
| Net Capacity           | 276 Litres                       |
| Operation              | 0°C - 6°C                        |
| Refrigerant            | R290                             |
| Climate Class          | 4                                |
| Max Ambient            | 38°C                             |
| Power                  | 230VAC / 50Hz<br>10A plug & lead |

95 x 700 x 840 3kg 25 x 730 x 880 7kg 76 Litres C - 6°C 90 °C 30VAC / 50Hz / 0.33kW A plug & lead





FRONT VIEW

SIDE VIEW





Revision: A - 19/09/2022 - 03 www.stoddart.com.au www.stoddart.co.nz