



## Freezer Undercounter 2 Door - 1/1GN

## **Product Information:**

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (-16° -20°C)
- Fan forced ducted cooling for uniformed performance throughout the entire freezer
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard
- 1/1GN shelf configuration with adjustable runners
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Self-closing doors with lock fitted as standard
- Supplied on standard and lockable castors for a 840mm finish height. Optional spacer to increase to 900mm working height
- 3 door model also available



## **Optional Accessories:**

- Height increase channel spacer pair (AXR.UCGN.CH) (2 required)
- 1/1GN shelf with runners (AXR.UCGN.SHELFKIT)

## **Specifications**

Model AXF.UCGN.2 W x D x H (mm) 1360 x 700 x 840


Weight 107kg

Packed Dimensions (mm) 1390 x 730 x 880

**Packed Weight** 126kg **Net Capacity** 184 Litres Operation -16°C - -20°C Refrigerant R290 Climate Class Max Ambient 38°C

230VAC / 50Hz / 0.53kW 10A plug & lead Power





Due to continuous product research and development, the information contained herein is subject to change without notice.



www.stoddart.com.au www.stoddart.co.nz

