



The ecomax 702 Utensil Washer offers the best wash result for hard baked in dirt. Perfect for utensils like pots, pans, trays or boxes.

## **Utensil Washer ecomax 702**

Cycle times*	120/360 sec
Capacity per hour*	up to 30 cycles
Wash/rinse temperature	60 – 65°C / min 82°C
Tank capacity	80 I
Fresh water consumption/cycle	4.5 I
Wash pump	2.9 kW
Heating booster/tank	9 kW / 3.3 kW
Total loading	12 kW
Rated voltage	400 V / 50 hz / 3N
Width/Depth/Height	780/945/1,765 mm
Loading height	630 mm
Rack size	600 x 760 mm

\*hot water connection

Connection to cold water or reduced voltage can extend the heating time and the program runtime. We recommend an external water softener for feed water hardness above 3°dH.The installation of machines with integrated water softener requires a back flow safety device (at site) according to DVGW-DIN 1988.

Line pressure required: 0,5 to 10 bar

## **PRODUCT ADVANTAGES**

- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- Deep-drawn wash tank bottom, no hygiene problems with corners and edges
- Thermostop-function for guaranteed rinse temperatures
- Removal of wash and rinse arms without any tools
- Easy access to all parts
- Flat surface of control panel
- Loading of high trays and pots: up to 630 mm loading height
- 150 mm floor clearance
- Electronic control
- Made completely out of stainless steel
- Tank covered with strainer made of stainless steel

## STANDARD EQUIPMENT

- Heater with thermostat control
- Pressure pump
- Electric cable, flexible water supply hose and drain hose



Units 9 & 10 124-130 Auburn Street Wollongong

02 4226 9779 info@kwikhe.com.au

kwikhe.com.au



